CNCGLASS
CNC Ucolin Interlayer Technology Co., Ltd.
SHENZHEN, GD, CHINA
Peter Lin · cnc@cncglass.com · WhatsApp / Mobile +86 15013829504
WeChat wecan365 · www.cncglass.com

How EVA Interlayers Are Manufactured

Why the manufacturing route matters

EVA used as an interlayer or a photovoltaic encapsulant is a thermoplastic copolymer of ethylene and vinyl acetate, later formed into a sheet with a controlled thickness and surface. Its clarity, adhesion, and weathering decide whether a module or a laminate will last. Those properties are made, not declared, so the production route is part of the product.




Figure 1. The manufacturing sequence: resin selection, compounding, extrusion or calendering, cooling and winding, then inspection.

From resin to a wound roll

The work starts with resin and additives chosen for the grade: vinyl acetate content, peroxide or other cross-linking system, ultraviolet stabilizers, and any optical modifiers. The melt is plasticized and homogenized, then extruded or calendered through a die or a roll stack that sets width, gauge, and surface texture. A sheet that is too thin may not protect or fill; a sheet that is too thick can hurt optical path or waste material. Cooling must stabilize the film without freezing in residual stress. Trimming, winding, and packaging follow, with an interleaf or a sealed wrap as the grade requires.

Quality control sits on every step: incoming resin checks, temperature and pressure in the melt, on-line thickness, and finished-roll tests for clarity, gel potential, and cleanliness. A sheet that will be laminated to glass or to cells also has to meet the handling and environmental expectations of the plant that will use it. As module and architectural demand grow, the same sequence will be held to tighter gauges and cleaner rooms, but the logic will not change: the roll is only as good as the process that made it.

Manufacturing an EVA interlayer is a controlled path from resin to a wound, inspected sheet. Formulation, melt, forming, cooling, and testing each decide whether the film will bond, stay clear, and last. That is the process we ask customers to understand when they judge a grade.

Contact Us

Brand: CNCGLASS

Company: CNC Ucolin Interlayer Technology Co., Ltd.
Address: SHENZHEN, GD, CHINA
Contact: Peter Lin
Email: cnc@cncglass.com
WhatsApp / Mobile: +86 15013829504
WeChat: wecan365
Website: www.cncglass.com

We can discuss EVA production quality targets and how a given grade should be stored and laminated.